

### Product Name:

## Jeger Wood Paint

### Product Description:

A new-generation semi-matte enamel for wood and metal. Suitable for exterior and interior use. Provides a flexible coating with good mechanical resistance. Easy to apply and quick-drying. Resistant to atmospheric conditions and protects against fungi growth.

### Recommended Use:

Decorative and protective painting of wooden and metal surfaces indoors and outdoors.

### Surface Preparation:

The surface must be dry, clean, and durable. Remove damaged (e.g., flaking and cracked) paint layers. Fill in any surface gaps. Clean previously painted surfaces from contaminants, grease, and rust. In case of fungi or mold, remove them using an appropriate preparation.

### Product Preparation:

- ✓ Mix the enamel thoroughly before use.
- ✓ Do not mix with other products.
- ✓ If using multiple packages from different production batches, mix them in a larger container to avoid color shade differences.

### Application:

Apply with a roller, brush, or spray. For spray application, dilute with up to 2% water if necessary. Apply at a temperature between +8°C to +25°C and relative humidity not exceeding 82%. Apply the next layer after a minimum of 2 hours. Clean tools with warm water after use.

### Drying Time:

At +23°C and 50% relative humidity, subsequent layers can be applied after approximately 2 hours. Low temperatures, high humidity, and poor ventilation extend drying time.

### Technical Parameters:

VOC Content UE 2004/42	Category II/Ag: EU limit value: 130 g/l (2010). This product contains less than 15 g/l VOC
Density at 20°C [g/cm <sup>3</sup> ]	1.15–1.25 g/cm <sup>3</sup>
Gloss level PNC 81914:2002	Semi-matte
Number of layers	2 (depending on color)
Solvent	Water

### Coverage:

Up to 12 m<sup>2</sup>/L per single coat. Practical coverage depends on factors such as substrate type, absorption, texture, application method, and color..

### Shelf Life:

24 months from production date.

### Packaging:

Available in 0.7L, 2.5L, and 5L.

The information in the technical data sheet is not exhaustive, it is based on laboratory tests, our knowledge and practical experience. They are aimed at ensuring the optimal use of the product, however, they are not the basis for legal liability of the Manufacturer due to the inability to control the conditions of the application. The quality of the product is guaranteed by our production system in accordance with the requirements of ISO 9001. We reserve the right to change the information provided without prior notice  
GLOBAL POINT Sp. z o.o. Sp. Komandytowa  
ul. Rozwoju 3, Biskupice Podgórne 55-040 Kobierzyce  
Telefon: 887 71 71 04  
jeger@jeger.pl

Date : 27.04.2022

### Environmental Protection:

Do not pour product residues into drains. Dispose of empty and unused containers in designated waste bins according to local regulations.

### Storage and Transport:

Store and transport the product in its original packaging, protected from weather conditions, at temperatures between +5°C and +25°C.

### Safety:

Keep out of reach of children. Contains tetrahydro-1,3,4,6-tetrakis (hydroxymethyl) imidazo[4,5-d]-imidazolo-2,5(1H,3H)-dione; 2-methylisothiazol-3(2H), 1,2-benzisothiazol-2(2H)-one, and a post-reaction mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1), which may cause an allergic reaction. If necessary, seek medical advice. Avoid inhaling mist or spray. Work in well-ventilated areas and use personal protective equipment. Dispose of contents/container in appropriately marked waste containers according to national regulations. VOC content limit (category A/a/FW) in the container: 30g/L (2010). This product contains less than 5g/L VOC.

The information in the technical data sheet is not exhaustive, it is based on laboratory tests, our knowledge and practical experience. They are aimed at ensuring the optimal use of the product, however, they are not the basis for legal liability of the Manufacturer due to the inability to control the conditions of the application. The quality of the product is guaranteed by our production system in accordance with the requirements of ISO 9001. We reserve the right to change the information provided without prior notice

GLOBAL POINT Sp. z o.o. Sp. Komandytowa  
ul. Rozwoju 3, Biskupice Podgórne 55-040 Kobierzyce  
Telefon: 887 71 71 04  
jeger@jeger.pl

Date : 27.04.2022