

### Product Name:

## Jeger Preservative Primer

### Product Description:

A water-based impregnating primer for wood. Designed to deeply penetrate the wood structure, increasing resistance to moisture and biological degradation. Prepares the surface for further coating with decorative or protective products.

### Recommended Use:

For priming wooden surfaces, both interior and exterior, to enhance adhesion and durability of subsequent coatings.

### Surface Preparation:

The surface must be dry, clean, and stable. Remove old and damaged paint or varnish layers. Sand the surface lightly and remove dust. Ensure all gaps or irregularities are filled and smoothed before application.

### Product Preparation:

- ✓ Mix the product thoroughly before use.
- ✓ Do not mix with other products or dilute with water.
- ✓ Use directly on the prepared surface.

### Application:

Apply with a brush, roller, or spray onto the properly prepared substrate. Apply at a temperature between +8°C and +25°C and relative humidity not exceeding 82%. Allow the surface to dry completely before applying any topcoat. Clean tools with warm water immediately after use.

The information in the technical data sheet is not exhaustive, it is based on laboratory tests, our knowledge and practical experience. They are aimed at ensuring the optimal use of the product, however, they are not the basis for legal liability of the Manufacturer due to the inability to control the conditions of the application. The quality of the product is guaranteed by our production system in accordance with the requirements of ISO 9001. We reserve the right to change the information provided without prior notice

GLOBAL POINT Sp. z o.o. Sp. Komandytowa  
ul. Rozwoju 3, Biskupice Podgórne 55-040 Kobierzyce  
Telefon: 887 71 71 04  
jeger@jeger.pl

DATE 27.04.2022

### Drying Time:

At +23°C and 50% relative humidity, the impregnating primer is dry to the touch after approximately 2 hours. Low temperatures, high humidity, and poor ventilation extend drying time.

### Technical Parameters:

VOC Content UE 2004/42	Category A/h. EU limit value: 130 g/l (2010). This product contains less than 20 g/l VOC.
Density at 20°C [g/cm <sup>3</sup> ]	1.00 ± 0.05 g/cm <sup>3</sup>
Gloss level PNC 81914:2002	MAT
Number of layers	1-2 (depending on color)
Solvent	Water

### Coverage:

Covers up to 10-12 m<sup>2</sup>/L per single coat. Practical coverage depends on substrate type, absorption, and application method.

### Shelf Life:

24 months from production date.

### Packaging:

Available in 0.7L, 2.5L, and 5L.

The information in the technical data sheet is not exhaustive, it is based on laboratory tests, our knowledge and practical experience. They are aimed at ensuring the optimal use of the product, however, they are not the basis for legal liability of the Manufacturer due to the inability to control the conditions of the application. The quality of the product is guaranteed by our production system in accordance with the requirements of ISO 9001. We reserve the right to change the information provided without prior notice

GLOBAL POINT Sp. z o.o. Sp. Komandytowa  
ul. Rozwoju 3, Biskupice Podgórne 55-040 Kobierzyce  
Telefon: 887 71 71 04  
jeger@jeger.pl

Date : 27.04.2022

### Environmental Protection:

Do not pour product residues into drains. Dispose of empty and unused containers in designated waste bins according to local regulations.

### Storage and Transport:

Store and transport the product in its original packaging, protected from weather conditions, at temperatures between +5°C and +25°C.

### Safety:

Keep out of reach of children. Contains tetrahydro-1,3,4,6-tetrakis (hydroxymethyl) imidazo[4,5-d]-imidazolo-2,5(1H,3H)-dione; 2-methylisothiazol-3(2H), 1,2-benzisothiazol-2(2H)-one, and a post-reaction mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1), which may cause an allergic reaction. If necessary, seek medical advice. Avoid inhaling mist or spray. Work in well-ventilated areas and use personal protective equipment. Dispose of contents/container in appropriately marked waste containers according to national regulations. VOC content limit (category A/a/FW) in the container: 130g/L (2010). This product contains less than 20g/L VOC.

The information in the technical data sheet is not exhaustive, it is based on laboratory tests, our knowledge and practical experience. They are aimed at ensuring the optimal use of the product, however, they are not the basis for legal liability of the Manufacturer due to the inability to control the conditions of the application. The quality of the product is guaranteed by our production system in accordance with the requirements of ISO 9001. We reserve the right to change the information provided without prior notice

GLOBAL POINT Sp. z o.o. Sp. Komandytowa  
ul. Rozwoju 3, Biskupice Podgórne 55-040 Kobierzyce  
Telefon: 887 71 71 04  
jeger@jeger.pl

Date : 27.04.2022