

### PRODUCT NAME

### WALLPAPER GLUE

### PRODUCT DESCRIPTION

Ready-to-use wallpaper paste

### APPLICATION

Bonding of vinyl wallpaper up to 370 g/m<sup>2</sup>. Ensures good adhesion of the wallpaper to the substrate. The product is characterised by high adhesion, moisture resistance and high performance.

### SUBSTRATE PREPARATION

The substrate should be smooth, dry, clean and durable. Remove old wallpaper, fill cavities and cracks and level, clean the surface. Particularly absorbent substrates should be primed beforehand.

### PRODUCT PREPARATION

- ✓ Mix the product before use.
- ✓ Do not dilute.
- ✓ Do not mix with other products.

### APPLICATION

**Methods:** roller, brush

Apply evenly directly to the wall, remove excess adhesive with a sponge or damp cloth. Apply at a temperature of +10°C to +25°C, at a relative humidity of max. 82%, avoid draughts. Once the product has been opened, use it all up. Wash the tools with warm water after use. Wash the painting tools with warm water after use.

### EFFICIENCY

5-6m<sup>2</sup> from 1 kg of product.

### EXPIRY DATE

24 months from date of manufacture

### PACKAGING

1kg, 3kg

The information contained in the technical data sheet is not exhaustive and is based on laboratory tests, our knowledge and practical experience. They are intended to ensure optimum use of the product, but do not form the basis of any legal liability on the part of the manufacturer due to the impossibility of controlling application conditions. **Product quality is guaranteed by our ISO 9001 compliant production system.** We reserve the right to change the information provided without prior notice.

Update date: 28.09.2022

### ENVIRONMENTAL PROTECTION

Do not pour product residues into the sewage system. Empty packaging and packaging with product residue that will no longer be used should be disposed of in a properly labelled waste container in accordance with national regulations.

### STORAGE AND TRANSPORT

The product should be transported and stored in its original packaging, protected from the weather. The storage and transport temperature is between +5°C and +30°C. Expiry date and batch number on the packaging.

### SECURITY

Keep out of the reach of children. This product contains 2-methylisothiazol-3(2H), 1,2-benzisothiazol-2(2H)-one and a post-reaction mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May cause an allergic reaction. Seek medical advice if necessary. Avoid inhalation of spray or mist. Work in well-ventilated areas. Wear personal protective equipment. Dispose of contents/container in appropriately labelled waste containers in accordance with national regulations.

The information contained in the technical data sheet is not exhaustive and is based on laboratory tests, our knowledge and practical experience. They are intended to ensure optimum use of the product, but do not form the basis of any legal liability on the part of the manufacturer due to the impossibility of controlling application conditions. **Product quality is guaranteed by our ISO 9001 compliant production system.** We reserve the right to change the information provided without prior notice.

Update date: 28.09.2022