

Technical sheet

PRODUCT NAME

Decorative pearl patina

PRODUCT DESCRIPTION

Decorative pearl patina is a semi-transparent decorative effect for walls. It gives the painted surface a delicate pearlescent shade, brightening up interiors.

APPLICATION

The effect is intended for application to walls. Particularly recommended for all kinds of decorative "patinas". Patina can be applied to plaster, concrete, stone, gypsum boards, wood-like boards and all load-bearing substrates.

SUBSTRATE PREPARATION

The substrate should be dry, clean and durable. Remove any damaged (e.g. flaking and cracked) coating of previous paints, adhesive and lime paints. Fill in surface defects and sand down. Clean previously painted surfaces of any impurities that hinder product adhesion, e.g. dust, greasy stains, rust, fungus and mould.

PRODUCT PREPARATION

- ✓ Mix the product thoroughly before use.
- ✓ Do not mix with other products.
- ✓ Do not dilute with water

APPLICATION

Methods: brush, roller or sponge

Apply the patina with a brush, roller or sponge using the wet-on-wet method and leave to dry for 3 hours. After this time, apply a second coat to increase the effect. Apply at a temperature of +8°C to +25°C, with a maximum relative humidity of 82%, avoiding draughts. Allow to dry for approx. 4 hours. Wash the painting tools with warm water after use.

Note: It is advisable to try the varnish on an inconspicuous area before painting the whole thing.

a fragment of the decorated surface.

DRYING TIME

At +23°C, 50% relative humidity, the product is dry after 2-4 hours, apply the next coat after this time. Low temperatures, increased humidity and poor ventilation prolong the drying time.

EFFICIENCY

up to 8 m²/L Effectiveness depends on substrate texture and absorbency, number of coats, application thickness, application method and contractor experience .

The information contained in the technical data sheet is not exhaustive and is based on laboratory tests, our knowledge and practical experience. They are intended to ensure optimum use of the product, but do not form the basis of any legal liability on the part of the manufacturer due to the impossibility of controlling application conditions. **Product quality is guaranteed by our ISO 9001 compliant production system.** We reserve the right to change the information provided without prior notice.

Update date:18.11.2022



GLOBAL POINT Sp. z o.o. Sp. Komandytowa 3 Development Street, Biskupice Podgórne55-040 Kohierzyce

Telephone: 887 71 71 04

jeger@jeger.pl



Technical sheet

EXPIRY DATE

24 months from date of manufacture

PACKAGING

0,75L

ENVIRONMENTAL PROTECTION

Do not pour product residues into the sewage system. Empty packaging and packaging with product residue that will no longer be used should be disposed of in an appropriately labelled waste container in accordance with national regulations.

STORAGE AND TRANSPORT

The product should be transported and stored in its original packaging, protected from the weather. The storage and transport temperature is between +5°C and +25°C. Expiry date and batch number on the packaging.

SECURITY

Keep out of the reach of children. This product contains tetrahydro-1,3,4,6-tetrakis (hydroxymethyl) imidazo[4,5-d] midazol-2,5(1H,3H)-dione and a post-reaction mixture of 5-chloro-2-methyl-2H- isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) and 1,2-benzoisothiazolin-3-one. May cause an allergic reaction. Seek medical advice if necessary. Avoid inhalation of spray or mist. Work in well-ventilated areas. Wear personal protective equipment. Dispose of contents/container in appropriately labelled waste containers in accordance with national regulations. VOC limit (Cat. A/e/FW) in package 130g/L (2010). This product contains less than 45g/I VOC.

The information contained in the technical data sheet is not exhaustive and is based on laboratory tests, our knowledge and practical experience. They are intended to ensure optimum use of the product, but do not form the basis of any legal liability on the part of the manufacturer due to the impossibility of controlling application conditions. **Product quality is guaranteed by our ISO 9001 compliant production system.** We reserve the right to change the information provided without prior notice.

Update date:18.11.2022



GLOBAL POINT Sp. z o.o. Sp. Komandytowa 3 Development Street, Biskupice Podgórne55-040 Kobierzyce

Telephone: 887 71 71 04

jeger@jeger.pl