

### PRODUCT NAME

#### Primer Loft Concrete for wall tiles and worktops

### PRODUCT DESCRIPTION

A priming primer that is essential before using Jeger Loft Concrete product on tiles and worktops. Provides adhesion to difficult substrates such as painted wood, laminate, glass, stainless steel, aluminium, PVC, porcelain, etc.

### APPLICATION

The product is designed for priming substrates such as varnished wood, laminate, glass, steel, stainless steel, aluminium, PVC, porcelain etc. before applying Jeger Loft Concrete.

### SUBSTRATE PREPARATION

The substrate should be dry, clean and durable. Wash and degrease the surface (in the case of stainless steel, it is recommended to matt the substrate). Sand the surface and vacuum.

### PRODUCT PREPARATION

- ✓ Shake the product well before use.
- ✓ Do not mix with other products.
- ✓ Do not dilute with water

### APPLICATION

#### Methods: roller

Apply the first layer of foundation with a medium-bristle roller. Apply in a criss-cross motion. You can keep the joints on the wall tiles. However, we advise that after applying Loft Concrete Primer and before coating with Loft Concrete product, coat the joints with Jeger Levelling Primer for Wall Tiles and Worktops to achieve a smooth surface. Apply the product to the properly prepared substrate with a roller or brush at +15°C to +25°C. Allow to dry for approx. 6 hours.

### DRYING TIME

At +23°C and 50% relative humidity, the product dries in about 6 hours. Low temperatures, increased humidity and poor ventilation prolong the drying time.

### EFFICIENCY

Up to 10m<sup>2</sup>/L with one coat of paint. Practical performance depends on factors such as the type, absorbency and texture of the substrate.

The information contained in the technical data sheet is not exhaustive and is based on laboratory tests, our knowledge and practical experience. They are intended to ensure optimum use of the product, but do not form the basis of any legal liability on the part of the manufacturer due to the impossibility of controlling application conditions. **Product quality is guaranteed by our ISO 9001 compliant production system.** We reserve the right to change the information provided without prior notice.

Update date: 08.05.2025

### EXPIRY DATE

12 months from date of manufacture

### PACKAGING

1L

### ENVIRONMENTAL PROTECTION

Do not pour product residues into the sewage system. Empty packaging and packaging with product residue that will no longer be used should be disposed of in a properly labelled waste container in accordance with national regulations.

### STORAGE AND TRANSPORT

The product should be transported and stored in its original packaging, protected from the weather. The storage and transport temperature is between +5°C and +25<sup>(o)</sup> °C. Expiry date and batch number on the packaging.

### SECURITY

Keep out of the reach of children. Product contains 1,2-benzisothiazol-3(2H)-one; post-reaction mass of 5- chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May cause an allergic reaction. Seek medical advice if necessary. Avoid inhalation of spray or mist. Work in well-ventilated areas. Wear personal protective equipment. Dispose of contents/container in appropriately labelled waste containers in accordance with national regulations. VOC limit (Cat. A/and/FW) in package 140g/L (2010). This product contains less than 5g/l VOC. Safety data sheet, instructions and detailed product safety information available at: [jeger.co.uk/info](http://jeger.co.uk/info)

The information contained in the technical data sheet is not exhaustive and is based on laboratory tests, our knowledge and practical experience. They are intended to ensure optimum use of the product, but do not form the basis of any legal liability on the part of the manufacturer due to the impossibility of controlling application conditions. **Product quality is guaranteed by our ISO 9001 compliant production system.** We reserve the right to change the information provided without prior notice.

Update date: 08.05.2025