

PRODUCT NAME

Primer Loft Concrete for cement floors and floor tiles

PRODUCT DESCRIPTION

A specialised white primer for concrete floors or floor tiles, the application of which is essential before using Jeger Loft Concrete product.

APPLICATION

A product designed for priming concrete floors and tiles before laying Jeger Loft Concrete.

Note: Do not use on floors in areas intended for industrial use or intensive use.

SUBSTRATE PREPARATION

from raw concrete and tiles, wash thoroughly and rinse with water, leave to dry.

PRODUCT PREPARATION

- ✓ Shake the product well before use.
- ✓ Do not mix with other products.

APPLICATION

Methods: roller

Dilute 1/3 of the contents of the pack (1:1) by adding an equal quantity of water. With the product thus prepared, apply the first coat with a roller in a crosswise motion. Let dry for about 4 hours. Then apply a second coat using the remaining undiluted product. After ±12h you can apply Jeger Loft Concrete effect. After painting, wash the painting tools with warm water.

DRYING TIME

At +23°C and 50% relative humidity, the product dries in about 4 hours. Low temperatures, increased humidity and poor ventilation prolong the drying time.

EFFICIENCY

Up to 10m²/L with one coat of paint. Practical performance depends on factors such as the type, absorbency and texture of the substrate.

EXPIRY DATE

12 months from date of manufacture

PACKAGING

1L

The information contained in the technical data sheet is not exhaustive and is based on laboratory tests, our knowledge and practical experience. They are intended to ensure optimum use of the product, but do not form the basis of any legal liability on the part of the manufacturer due to the impossibility of controlling application conditions. **Product quality is guaranteed by our ISO 9001 compliant production system.** We reserve the right to change the information provided without prior notice.
GLOBAL POINT Sp. z o.o. Sp. Komandytowa
3 Development Street, Biskupice Podgórne55-040
Kobierzyce
Telephone: 887 71 71 04
jeger@jeger.pl

Update date: 14.10.2022

ENVIRONMENTAL PROTECTION

Do not pour product residues into the sewage system. Empty packaging and packaging with product residue that will no longer be used should be disposed of in an appropriately labelled waste container in accordance with national regulations.

STORAGE AND TRANSPORT

The product should be transported and stored in its original packaging, protected from the weather. The storage and transport temperature is between +5°C and +25^(o) °C. Expiry date and batch number on the packaging.

SECURITY

Keep out of the reach of children. This product contains 1,2-benzisothiazolin-3-one and a post-reaction mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May cause an allergic reaction. Seek medical advice if necessary. Avoid inhalation of spray or mist. Work in well-ventilated areas. Wear personal protective equipment. Dispose of contents/container in appropriately labelled waste containers in accordance with national regulations. VOC limit (Cat. A/and/FW) in package 140g/L (2010). This product contains less than 5g/l VOC.

The information contained in the technical data sheet is not exhaustive and is based on laboratory tests, our knowledge and practical experience. They are intended to ensure optimum use of the product, but do not form the basis of any legal liability on the part of the manufacturer due to the impossibility of controlling application conditions. **Product quality is guaranteed by our ISO 9001 compliant production system.** We reserve the right to change the information provided without prior notice.

GLOBAL POINT Sp. z o.o. Sp. Komandytowa
3 Development Street, Biskupice Podgórne 55-040
Kobierzyce
Telephone: 887 71 71 04
jeger@jeger.pl

Update date: 14.10.2022