

PRODUCT NAME

Primer Nubia Black

PRODUCT DESCRIPTION

Black primer under the Jeger Nubia decorative effect. It evens out the absorbency of the substrate, strengthens and increases the adhesion of the decorative effect and allows for proper application to achieve the desired effect.

APPLICATION

Preparation of the substrate for the correct application of Jeger Nubia decorative effect.

SUBSTRATE PREPARATION

The substrate should be dry, clean and durable. Remove any damaged (e.g. flaking and cracked) coating of previous paints, adhesive and lime paints. Fill surface defects with a suitable filler and sand down. Clean previously painted surfaces of any impurities that may hinder paint adhesion, e.g. dust, greasy stains, rust, fungus and mould.

PRODUCT PREPARATION

- ✓ Primer should be mixed thoroughly before use.
- ✓ Do not mix with other products.
- ✓ Do not dilute with water.

APPLICATION

Methods: roller

Apply the first coat with a microfibre roller spreading it in a criss-cross motion, irregularly in all directions. Allow to dry for 2h. After this time, the surface can be covered with the decorative effect. If necessary, if there are clear colour bleeds in the substrate, apply a second coat of Jeger Primer Nubia Black. Apply at a temperature of +8°C to +25°C, at a relative humidity of max. 82%, avoiding draughts. Wash tools with warm water after use.

DRYING TIME

At +23°C and 50% relative humidity, the primer is dry to the touch after approx. 1 hour. Low temperatures, increased humidity and poor ventilation prolong the drying time.

The information contained in the technical data sheet is not exhaustive and is based on laboratory tests, our knowledge and practical experience. They are intended to ensure optimum use of the product, but do not form the basis of any legal liability on the part of the manufacturer due to the impossibility of controlling application conditions. **Product quality is guaranteed by our ISO 9001 compliant production system.** We reserve the right to change the information provided without prior notice.

Update date: 12.11.2024

TECHNICAL SPECIFICATIONS

Volatile Organic Compounds (VOCs) in the container EU Directive 2004/42	Category A/g/FW: EU limit value: VOC (cat A/g/FW) in a package of 30g/L (2010). This product contains less than 10g/l VOC.
Density 20°C [g/cm ³].	1,37± 2%
Degree of gloss EN 13300	Deep - Mat
Number of layers	1-2
Solvent	Water

EFFICIENCY

± 8m² from 1l packaging. Performance depends on the structure and absorbency of the substrate, thickness and number of coats, application method and experience of the contractor

EXPIRY DATE

24 months from date of manufacture

PACKAGING

1l,

ENVIRONMENTAL PROTECTION

Do not pour product residues into the sewage system. Empty packaging and packaging with product residue that will no longer be used should be disposed of in an appropriately labelled waste container in accordance with national regulations.

STORAGE AND TRANSPORT

The product should be transported and stored in its original packaging, protected from the weather. The storage and transport temperature is between +5°C and +25°C. Expiry date and batch number on the packaging.

SECURITY

Keep out of the reach of children. This product contains Tetrahydro-1,3,4,6-tetrakis (hydroxymethyl) imidazo[4,5-d] midazol-2,5(1H,3H)-dione, 2- methyl-2H-isothiazol-3-one and a post-reaction mixture of 5-chloro-2-methyl-2H-isothiazol-3-one, 2- methyl-2H-isothiazol-3-one (3:1). May cause an allergic reaction. Seek medical advice if necessary. Avoid inhalation of spray or mist. Work in well-ventilated areas. Wear personal protective equipment. Dispose of contents/container in appropriately labelled waste containers in accordance with national regulations. VOC limit (Cat. A/G/FW) in package 30g/L (2010). This product contains less than 10g/l VOC.

The information contained in the technical data sheet is not exhaustive and is based on laboratory tests, our knowledge and practical experience. They are intended to ensure optimum use of the product, but do not form the basis of any legal liability on the part of the manufacturer due to the impossibility of controlling application conditions. **Product quality is guaranteed by our ISO 9001 compliant production system.** We reserve the right to change the information provided without prior notice.

Update date: 12.11.2024

PRODUCT NAME

Primer Nubia White

PRODUCT DESCRIPTION

White primer under the Jeger Nubia decorative effect. It evens out the absorbency of the substrate, strengthens and increases the adhesion of the decorative effect and allows for proper application to achieve the desired effect.

APPLICATION

Preparing the substrate for the correct application of Jeger Nubia decorative effect.

SUBSTRATE PREPARATION

The substrate should be dry, clean and durable. Remove any damaged (e.g. flaking and cracked) coating of previous paints, adhesive and lime paints. Fill surface defects with a suitable filler and sand down. Clean previously painted surfaces of any impurities that may hinder paint adhesion, e.g. dust, greasy stains, rust, fungus and mould.

PRODUCT PREPARATION

- ✓ Primer should be mixed thoroughly before use.
- ✓ Do not mix with other products.
- ✓ Do not dilute with water.

APPLICATION

Methods: roller

Apply the first coat with a microfibre roller by spreading it in a criss-cross motion, irregularly in all directions. Allow to dry for 2h. After this time, the surface can be covered with the decorative effect. If necessary, if there are clear colour breakthroughs in the substrate, apply a second coat of Jeger Primer Nubia Black. Apply at a temperature of +8°C to +25°C, at a relative humidity of max. 82%, avoiding draughts. Wash tools with warm water after use.

DRYING TIME

At +23°C and 50% relative humidity, the primer is dry to the touch after approx. 1 hour. Low temperatures, increased humidity and poor ventilation prolong the drying time.

The information contained in the technical data sheet is not exhaustive and is based on laboratory tests, our knowledge and practical experience. They are intended to ensure optimum use of the product, but do not form the basis of any legal liability on the part of the manufacturer due to the impossibility of controlling application conditions. **Product quality is guaranteed by our ISO 9001 compliant production system.** We reserve the right to change the information provided without prior notice.

Update date: 12.11.2024

TECHNICAL SPECIFICATIONS

Volatile Organic Compounds (VOCs) in the container EU Directive 2004/42	Category A/g/FW: EU limit value: VOC (cat A/g/FW) in a package of 30g/L (2010). This product contains less than 10g/l VOC.
Density 20°C [g/cm ³].	1,37± 2%
Degree of gloss EN 13300	Deep - Mat
Number of layers	1-2
Solvent	Water

EFFICIENCY

± 8m² from 1l packaging. Performance depends on the structure and absorbency of the substrate, thickness and number of coats, application method and experience of the contractor

EXPIRY DATE

24 months from date of manufacture

PACKAGING

1l,

ENVIRONMENTAL PROTECTION

Do not pour product residues into the sewage system. Empty packaging and packaging with product residue that will no longer be used should be disposed of in a properly labelled waste container in accordance with national regulations.

STORAGE AND TRANSPORT

The product should be transported and stored in its original packaging, protected from the weather. The storage and transport temperature is between +5°C and +25°C. Expiry date and batch number on the packaging.

SECURITY

Keep out of the reach of children. This product contains Tetrahydro-1,3,4,6-tetrakis (hydroxymethyl) imidazo[4,5-d] midazol-2,5(1H,3H)-dione, 2- methyl-2H-isothiazol-3-one and a post-reaction mixture of 5-chloro-2-methyl-2H-isothiazol-3-one, 2- methyl-2H-isothiazol-3-one (3:1). May cause an allergic reaction. Seek medical advice if necessary. Avoid inhalation of spray or mist. Work in well-ventilated areas. Wear personal protective equipment. Dispose of contents/container in appropriately labelled waste containers in accordance with national regulations. VOC limit (Cat. A/G/FW) in package 30g/L (2010). This product contains less than 10g/l VOC.

The information contained in the technical data sheet is not exhaustive and is based on laboratory tests, our knowledge and practical experience. They are intended to ensure optimum use of the product, but do not form the basis of any legal liability on the part of the manufacturer due to the impossibility of controlling application conditions. **Product quality is guaranteed by our ISO 9001 compliant production system.** We reserve the right to change the information provided without prior notice.

Update date: 12.11.2024