

PRODUCT NAME

PROTECTOR LOFT CONCRETE

PRODUCT DESCRIPTION

Two-component lacquer for protecting the Loft Concrete decorative effect on floors and walls exposed to constant contact with water. Provides durable protection and high resistance to abrasion and dirt. Creates a colourless, matt, smooth surface with high durability. The varnish is washable and resistant to mild cleaning agents.

APPLICATION

The lacquer is designed for use as a top coat (protective layer) for Loft Concrete on floors and walls in residential and public areas.

SUBSTRATE PREPARATION

The surface to be protected must be dry, cured, free of dust and dirt.

PRODUCT PREPARATION

Mix Protector component A (500ml) well, then add the entire contents of component B (100ml). Then add 60ml of water and thoroughly. Leave the container open for approximately 10 minutes, then mix again. The time the product can be used after mixing the ingredients is 1-2h. Drying time: 12h.

APPLICATION

Methods: roller

Apply the varnish to the properly prepared substrate with a high-quality roller (velour or microfibre) with 8 mm bristles. The second coat can be applied after 4 hours without sanding. Apply the varnish at a temperature between +15 °C and +25 ^(o) C.

DRYING TIME

At +23°C and 50% relative humidity, the product dries in about 12 hours. Apply another coat after approx. 4 hours. Low temperatures, increased humidity and poor ventilation prolong the drying time.

TECHNICAL SPECIFICATIONS

The information contained in the technical data sheet is not exhaustive and is based on laboratory tests, our knowledge and practical experience. They are intended to ensure optimum use of the product, but do not form the basis of any legal liability on the part of the manufacturer due to the impossibility of controlling application conditions. **Product quality is guaranteed by our ISO 9001 compliant production system.** We reserve the right to change the information provided without prior notice.

Update date: 08.05.2025

Volatile Organic Compounds (VOCs) in container EU Directive 2004/42	Category A/a/FW: EU limit value: 140 g/l (2010) This product contains 110.2 g/l VOC
Degree of gloss PNC 81914:2002	matt
Number of layers	2
Solvent	Water
Shelf life of the product after mixing A and B components	up to 2 hours

EFFICIENCY

0,08-0,1 kg/m². Performance depends on the structure and absorbency of the substrate, the thickness of the application, the application method and the experience of the contractor.

EXPIRY DATE

12 months from date of manufacture

PACKAGING

0,6l

ENVIRONMENTAL PROTECTION

Do not pour product residues into the sewage system. Empty packaging and packaging with product residue that will no longer be used should be disposed of in a properly labelled waste container in accordance with national regulations.

STORAGE AND TRANSPORT

The product should be transported and stored in its original packaging, protected from the weather. The storage and transport temperature is between +5°C and +25^(o) °C. Expiry date and batch number on the packaging.

SECURITY

Keep out of the reach of children. This product contains 2-methylisothiazol-3(2H), 1,2-benzisothiazol-2(2H)-one and a post-reaction mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). Hydrophilic aliphatic polyisocyanate based on HDI; Homopolymer of hexamethylene-1,6-diisocyanate; Hydrophilic aliphatic polyisocyanate based on IPDI;

Hexamethylene diisocyanate; hexane-1,6-diyl diisocyanate. May cause reaction allergic. Wear protective gloves. In case of contact, flush with water for several minutes. Seek medical advice if necessary. Avoid inhalation of sprayed liquid.

The information contained in the technical data sheet is not exhaustive and is based on laboratory tests, our knowledge and practical experience. They are intended to ensure optimum use of the product, but do not form the basis of any legal liability on the part of the manufacturer due to the impossibility of controlling application conditions. **Product quality is guaranteed by our ISO 9001 compliant production system.** We reserve the right to change the information provided without prior notice.

Update date: 08.05.2025

or mist. Work in well-ventilated areas. Use personal protective equipment. Dispose of contents/container in appropriately labelled waste containers in accordance with national regulations. VOC content limit (Cat. A/j/FW) per package 140g/L (2010). This product contains less than 110g/L VOC. Safety data sheet, instructions and detailed product safety information available at: jeger.co.uk/info.

The information contained in the technical data sheet is not exhaustive and is based on laboratory tests, our knowledge and practical experience. They are intended to ensure optimum use of the product, but do not form the basis of any legal liability on the part of the manufacturer due to the impossibility of controlling application conditions. **Product quality is guaranteed by our ISO 9001 compliant production system.** We reserve the right to change the information provided without prior notice.

Update date: 08.05.2025