

PRODUCT NAME

Loft Concrete Protector

PRODUCT DESCRIPTION

Jeger Loft Concrete Protector is a clear matt lacquer that protects surfaces against dirt and water. It creates a matt finish that is resistant to washing.

APPLICATION

The lacquer is intended for use as a protective layer for the Loft Concrete effect.

SUBSTRATE PREPARATION

The substrate should be dry, clean and durable. Clean previously painted surfaces of impurities that limit the adhesion of the varnish, e.g. dust, greasy stains, rust, fungus and mould.

PRODUCT PREPARATION

- ✓ The varnish should be mixed thoroughly before use.
- ✓ Do not mix the product with others.
- ✓ Do not dilute with water.
- ✓ If several packs from different production batches are used, they should be mixed in a larger pack to prevent differences in gloss.

APPLICATION

Methods: roller

Apply with a short bristle roller. Apply the varnish irregularly spreading in all directions, avoiding vertical and horizontal movements. Apply +8°C to +25°C, max. 82% relative humidity, avoiding draughts. Allow to dry for approx. 4 h. Wash the painting tools with warm water after use.

Note: The lacquer hardly changes the shade of the decorated surface. It is recommended to try the varnish on a barely visible part of the decorated surface before painting the whole thing.

DRYING TIME

At a temperature of +23°C and a relative humidity of 50%, the varnish is dry to the touch after approx. 2 hours. Subsequent coats should be applied after approx. 4 hours. Low temperatures, increased humidity and poor ventilation prolong the drying time.

The information contained in the technical data sheet is not exhaustive and is based on laboratory tests, our knowledge and practical experience. They are intended to ensure optimum use of the product, but do not form the basis of any legal liability on the part of the manufacturer due to the impossibility of controlling application conditions. **Product quality is guaranteed by our ISO 9001 compliant production system.** We reserve the right to change the information provided without prior notice.

Update date: 08.05.2025

TECHNICAL SPECIFICATIONS

| | |
|--|---|
| Volatile Organic Compounds (VOCs) in the container EU Directive 2004/42 | Category A/e/FW: EU limit value: VOC (cat. A/e/FW) in package 130g/L (2010). This product contains less than 45g/l VOC. |
| Density 20°C [g/cm ³]. | 1,05± 2% |
| Degree of gloss PNC 81914:2002 | matt |
| Number of layers | 1-2 |
| Solvent | Water |

EFFICIENCY

Up to 12m²/L in a single coat. Practical performance depends on factors such as the type, absorbency and texture of the substrate, the application method and the colour.

EXPIRY DATE

24 months from date of manufacture

PACKAGING

0,5l

ENVIRONMENTAL PROTECTION

Do not pour product residues into the sewage system. Empty packaging and packaging with product residue that will no longer be used should be disposed of in a properly labelled waste container in accordance with national regulations.

STORAGE AND TRANSPORT

The product should be transported and stored in its original packaging, protected from the weather. The storage and transport temperature is between +5°C and +25^(o) °C. Expiry date and batch number on the packaging.

SECURITY

Keep out of the reach of children. This product contains tetrahydro-1,3,4,6-tetrakis (hydroxymethyl) imidazo[4,5-d] midazol-2,5(1H,3H)-dione and a post-reaction mixture of 5-chloro-2-methyl-2H- isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) and 1,2-benzisothiazolin-3-one. May cause an allergic reaction. Seek medical advice if necessary. Avoid inhalation of spray or mist. Work in well-ventilated

The information contained in the technical data sheet is not exhaustive and is based on laboratory tests, our knowledge and practical experience. They are intended to ensure optimum use of the product, but do not form the basis of any legal liability on the part of the manufacturer due to the impossibility of controlling application conditions. **Product quality is guaranteed by our ISO 9001 compliant production system.** We reserve the right to change the information provided without prior notice.

Update date: 08.05.2025

premises. Use personal protective equipment. Dispose of contents/container in appropriately labelled waste containers in accordance with national regulations. VOC content limit (Cat. A/e/FW) per package 130g/L (2010). This product contains less than 45g/L VOC. Safety data sheet, instructions and detailed product safety information available at: jeger.co.uk/info

The information contained in the technical data sheet is not exhaustive and is based on laboratory tests, our knowledge and practical experience. They are intended to ensure optimum use of the product, but do not form the basis of any legal liability on the part of the manufacturer due to the impossibility of controlling application conditions. **Product quality is guaranteed by our ISO 9001 compliant production system.** We reserve the right to change the information provided without prior notice.

Update date: 08.05.2025