

### PRODUCT NAME

## CHALKY WAX

### PRODUCT DESCRIPTION

Chalky Wax - designed to decorate and protect furniture from water stains. It is ideal for use over Jeger chalk paint protecting and highlighting its colour. The wax gives the decorated surface a subtle shine.

### APPLICATION

Decorative and protective glossing of surfaces coated with Jeger Chalk Paint.

### SUBSTRATE PREPARATION

The substrate should be dry, clean and durable. Clean previously painted surfaces of impurities that limit the adhesion of the paint, e.g. dust, greasy stains, rust, fungi and mould.

### PRODUCT PREPARATION

- ✓ Mix the product before use.
- ✓ Do not dilute.
- ✓ Do not mix with other products.

### APPLICATION

**Methods:** brush, sponge, cloth

Apply a thin layer with a brush, sponge or cloth over the dried chalk paint. Allow to dry for approx. 2 h and polish gently with a dry cloth. Apply at a temperature of between +8°C and +25°C, at a relative humidity of max. 82%, avoid draughts. Wash the painting tools with warm water after painting.

Note: The wax may slightly alter the colour saturation. It is recommended that you try it on a barely visible surface before application.

### DRYING TIME

At +23°C and 50% relative humidity, dry after approx. 2 hours. Low temperatures, increased humidity and poor ventilation prolong the drying time and affect the polishability.

The information contained in the technical data sheet is not exhaustive and is based on laboratory tests, our knowledge and practical experience. They are intended to ensure optimum use of the product, but do not form the basis of any legal liability on the part of the manufacturer due to the impossibility of controlling application conditions. **Product quality is guaranteed by our ISO 9001 compliant production system.** We reserve the right to change the information provided without prior notice.

Update date: 11.03.2022

### EFFICIENCY

Up to 5m<sup>2</sup> from a 0.4L container with a single application. Practical performance depends on factors such as substrate type and texture, application method and colour.

### EXPIRY DATE

12 months from date of manufacture

### PACKAGING

0,4L

### ENVIRONMENTAL PROTECTION

Do not pour product residues into the sewage system. Empty packaging and packaging with product residue that will no longer be used should be disposed of in a properly labelled waste container in accordance with national regulations.

### STORAGE AND TRANSPORT

The product should be transported and stored in its original packaging, protected from the weather. The storage and transport temperature is between +5°C and +25°C. Expiry date and batch number on the packaging.

### SECURITY

Keep out of the reach of children. This product contains a post-reaction mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1), 2-methyl-2H-isothiazol-3-one and 1,2-benzisothiazolin-3-one. May cause an allergic reaction. Seek medical advice if necessary. Avoid inhalation of spray or mist. Work in well-ventilated areas. Wear personal protective equipment. Dispose of contents/container in appropriately labelled waste containers in accordance with national regulations. VOC content limit (Cat. A/L/FW) per package 200g/L (2010). This product contains less than 3g/l VOC.

The information contained in the technical data sheet is not exhaustive and is based on laboratory tests, our knowledge and practical experience. They are intended to ensure optimum use of the product, but do not form the basis of any legal liability on the part of the manufacturer due to the impossibility of controlling application conditions. **Product quality is guaranteed by our ISO 9001 compliant production system.** We reserve the right to change the information provided without prior notice.

Update date: 11.03.2022